



Index	2	Specifications	3
Safety information	2	Clamp mounting	4
Content	2	Cable information	5
Technical	3	List of symbols	6




## SAFETY INFORMATION




Make sure all connectors are connected properly




Use a source of AC power that complies with local electrical codes




Block access below the work area when maintaining the unit



Don't modify or install genuine parts on this product







Don't install in a flammable or explosive area




Disconnect the power supply before installing or maintaining

## CONTENT





## Tools









## SPECIFICATIONS




LED: 16 x Cree or Luxeon  
 Available colours: Extra warm white 2700K, Warm white 3000K, neutral white 4000K and fresh white 5000K  
 Lenses: 8°, 12°, 30°, 60°, 12x46°  
 Power supply: 200-240 VAC  
 Power consumption: Max. 20 Watt  
 Cable length: 200 cm  
 Housing: ABS / aluminum  
 Weight: 870 gr  
 IP value: IP20  
 Measurements: 74 x 180 x 180 mm (hxxwxd)  
 Ambient temperature: -10° C till +40° C

## ACCESSORIES

872010 CLS Dimmer electr. 1-10V for MT35/MTD44 LED driver  
 872019 CLS Dimmer Jung phase cut max. 270VA 230-240VAC  
 113000 CLS LDC-41 DMX LED dimmer 4 channels



# CABLE INFORMATION



2015 CLS LED BV. All rights reserved. Information subject to change without notice, CLS LED BV and all affiliated companies disclaim liability for injury, damage direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this manual. No part of this manual may be reproduced, in any form or by any means, without permission in writing from CLS LED BV. Other legal information can be found in our General conditions, found on the back of your CLS-LED BV invoice, inside the CLS catalogue or on our website [www.cls-led.com/voorwaarden.pdf](http://www.cls-led.com/voorwaarden.pdf)

# LIST OF SYMBOLS

	<b>Protection class</b> One, two or three		<b>IP value</b> Ingress Protection classifies the degrees of protection provided against the intrusion of the product
	<b>Application area</b> Indoor or outdoor		<b>Colour</b> Available colours; Amber, blue, red or green
	<b>Application area</b> Floor, wall or ceiling		<b>White colour temperature</b> In different Kelvin values; Cold white, neutral white, warm white or extra warm white
	<b>Swivel</b> Fixture is horizontally rotatable, indicated in degrees		<b>Colour changing</b> RGB, RGB-W, RGB-A or AWB
	<b>Swivel</b> Fixture is vertically rotatable, indicated in degrees		<b>Dynamic White</b> Stepless control of white light
	<b>Multiple connection</b> Daisychain connectivity		<b>Curve</b> Minimal bending curve in centimeters
	<b>Installation depth</b> In centimeters		<b>Cutting length</b> Indicated by the cutting marks
	<b>Installation size</b> In centimeters		<b>LED pitch</b> Pitch between the LEDs in millimeters
	<b>Cable length</b> Maximum cable attached to the fixture in centimeters		<b>Power supply</b> In VDC, VAC or milliAmpere
	<b>Driver</b> Inclusive or exclusive		<b>Power consumption</b> In VA or Watt
	<b>Weight</b> In grams/kilograms		<b>Dimmable</b> 1-10 Volt, Phase, individual or DMX dimmable
	<b>Pressure</b> Maximum pressure on the fixture in kg/cm <sup>2</sup>		<b>Magno dimming</b> Accurate dimming from 100 - 1% by using a magnet
	<b>Lifespan</b> Of the light source in hours		<b>DMX input</b> Fixture works on DMX512 protocol
	<b>Lenses</b> Available lenses, indicated in degrees		<b>Combined product</b> Compose your own fixture
	<b>LEDs</b> Kind of LED used in the fixture		<b>Warranty</b> 3 years warranty on the product
	<b>Plug &amp; play</b> Easy connection using the SmartConnect system		<b>Conformité Européenne</b> CE marking for free marketability of industrial goods within the EU
			<b>Energy label</b>