



Main features:

EN

Significant savings on energy- and maintenance costs. With a power consumption of max. 10 Watts, the REVO Compact Inground replaces halogen light sources of 75W and HGI fixtures up to 35 Watts.

Due to easily interchangeable lenses, beam angles from 8° to 54° plus elliptical are possible.

High grade stainless steel 316 top ring, for optimal protection against corrosion.

IP67 rating.

2/3/4 Way mold set included, for guaranteed waterproof connection.

NL

Enorme besparing op de energie- en onderhoudskosten. Met een opgenomen vermogen van slechts 10 Watt kunnen halogeen lichtbronnen tot 75 Watt en HGI lichtbronnen tot 35 Watt vervangen worden.

Dankzij eenvoudig verwisselbare lenzen zijn openingshoeken van 8° tot 54°, alsmede elliptical lichtbundels mogelijk.

RVS 316 afdekking voor optimale bescherming tegen corrosie.

IP67 classificatie.

De Revo Compact Inground wordt inclusief een gietmof set geleverd voor een optimale waterdichte aansluiting.



Configuring a REVO Compact Inground is extremely simple: Just choose from the different model options, housing colours, LED colours and lens types. Simply follow the steps in the overview below to obtain your REVO code.

1) REVO: RC

2) Model:

i REVO compact Inground

3) Housing colour:

2 Black anodised aluminum

4) LED colour:

01 Cold white 6300K
 02 Neutral white 4000K
 03 Warm white 3000K
 04 Extra warm white 2700K
 11 Red
 22 Royal blue
 31 Amber

5) Lens kit:

1 12° lenses (Spot)
 2 12 x 46° lenses (Elliptical)
 3 30° lenses (Medium Flood)
 4 54° lenses (Wide Flood)
 5 8° lenses (Superspot)

Example:

You would like to order a REVO Compact Inground with black housing, warm white LEDs and spot lenses; your unique REVO Compact Inground order number will be: RC-i-2-03-1.

