



CLS - Downlighters - MR16 series

Main features:

EN

With a power consumption of 4 Watts, an energy efficient replacement for 35 Watt halogen light sources.

Massive aluminum CNC cut housing for optimal cooling.

4 different mounting plates available.

Different beam angles.

Different LED colours available.

Dimming possible.

CLS SmartConnect system.

NL

Met een vermogen van slechts 4 Watt kunnen halogeenlampen tot 35 Watt vervangen worden.

CNC gefreesde massief aluminium behuizing voor optimale koeling.

4 verschillende montageplaten zijn leverbaar.

Verschillende licht openingshoeken.

Verschillende LED kleuren beschikbaar.

Dimbaar.

CLS SmartConnect systeem.



Products MR16 series:

120005



CLS MR16 flood fixture 40° 1 x TFFC warm white 2950K 1000mA, size ø 50 x 44 mm (øxh)

120020



CLS MR16 tilttable round ceiling unit 1 hole alu-brushed, size Ø 90 x 35 mm (øxh)

120025



CLS MR16 tilttable square ceiling unit 1 hole alu-brushed, size 90 x 90 x 35 mm (hxwd)

122400



CLS LON/ MR16 round ceiling unit alu-brushed, size ø 80 x 30 mm (øxh)

122405



CLS LON/ MR16 square ceiling unit alu-brushed, size 75 x 75 x 30 mm (hxwd)

