



CLS - Downlighters - Luxo 3 series

Main features:

EN

Single 7.6 Watt module can replace a 50 Watt halogen light source like MR16, AR 111.

High quality easy interchangeable lens optics in different beam angles; 25°, 40°, 60° and 120°.

Massive aluminum CNC cut housing for optimal cooling.

Anti glare design, optional diffusion filter for very soft light dispersion.

Each module is horizontally and vertically adjustable.

Round, square and dual mounting plate available.

Dimming possible.

CLS SmartConnect system.

NL

Met een vermogen van slechts 7,6 Watt kunnen halogeenlampen tot 50 Watt vervangen worden.

Keuze uit 25°, 40°, 60° en 120° licht openingshoek.

De hoogwaardige multilens is snel en eenvoudig te wisselen.

CNC gefreesde massief aluminium behuizing voor optimale koeling.

'Anti-glare' ontwerp. Soft tone diffusie filter optioneel leverbaar.

Elke module is horizontaal en verticaal verstelbaar.

Ronde, vierkante en tweevoudig rechthoekige montageplaat verkrijgbaar.

Dimbaar.

CLS SmartConnect systeem.



Products Luxo 3 series:

L-3-1-03-2



CLS Luxo 3, module, mfl 40°, 3 x Cree warm white 3000K, IP40, size ø 70 x 60 mm (øxh)

L-3-1-04-2



CLS Luxo 3, module, mfl 40°, 3 x Cree extra warm white 2700K, IP40, size ø 70 x 60 mm (øxh)

111099



CLS Soft diffusion filter for Luxo 3

111311



CLS Luxo 3 round ceiling unit alu-brushed 1 hole, size ø 90 x 42 mm (øxh)

111321



CLS Luxo 3 square ceiling unit alu-brushed 1 hole, size 42 x 90 x 90 mm (hxwxh)

111324



CLS Luxo 3 square ceiling unit alu-brushed 4 holes, size 42 x 172 x 172 mm (hxwxh)

111332



CLS Luxo 3 rectangular ceiling unit alu-brushed 2 holes, size 42 x 172 x 90 mm (hxwxh)

